



GP
ELECTRONICS

MMSZ5221B-5259B


Plastic-Encapsulate Diodes

MMSZ5221B-5259B ZENER DIODE

Feature

- Constant Voltage control
- Wide Voltage Range Selection 2.4V to 59V
- RoHS compliant / Green EMC
- Matte Tin (Sn) Lead finish

SOD-123



ABSOLUTE MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Power Dissipation	P_D	0.35	W
Junction Temperature	T_J	150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 ~ +125	$^{\circ}\text{C}$
Maximum Regulator Current	I_{ZM}	P_D/V_Z	mA

ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Type Number	Device Marking	V _z (V) @I _{zT} ^{*1}			I _{zT}	Z _{zT} @I _{zT}	Z _{zK} @I _{zK}	I _{zk}	I _R	V _R
		Nom(V)	Min(V)	Max(V)	mA	Ω		(mA)	(uA)	(V)
MMSZ5221B	C1	2.4	2.28	2.52	20	30	1200	0.25	100	1.0
MMSZ5223B	C3	2.7	2.57	2.84	20	30	1300	0.25	75	1.0
MMSZ5225B	C5	3.0	2.85	3.15	20	30	1600	0.25	50	1.0
MMSZ5226B	G1	3.3	3.14	3.47	20	28	1600	0.25	25	1.0
MMSZ5227B	G2	3.6	3.42	3.78	20	24	1700	0.25	15	1.0
MMSZ5228B	G3	3.9	3.71	4.10	20	23	1900	0.25	10	1.0
MMSZ5229B	G4	4.3	4.09	4.52	20	22	2000	0.25	5	1.0
MMSZ5230B	G5	4.7	4.47	4.94	20	19	1900	0.25	5	2.0
MMSZ5231B	E1	5.1	4.85	5.36	20	17	1600	0.25	5	2.0
MMSZ5232B	E2	5.6	5.32	5.88	20	11	1600	0.25	5	3.0
MMSZ5233B	E3	6.0	5.70	6.30	20	7	1600	0.25	5	3.5



Continued next page


ELECTRICAL CHARACTERISTICS (Ta=25°C unless otherwise noted)

Type Number	Device Marking	V _Z (V) @I _{ZT} ^{*1}			I _{ZT} mA	Z _{VT} @I _{ZT} Ω	Z _{ZK} @I _{ZK} Ω	I _{zk} (mA)	I _R (μA)	V _R (V)
		Nom(V)	Min(V)	Max(V)						
MMSZ5234B	E4	6.2	5.89	6.51	20	7	1000	0.25	5	4.0
MMSZ5235B	E5	6.8	6.46	7.14	20	5	750	0.25	3	5.0
MMSZ5236B	F1	7.5	7.13	7.88	20	6	500	0.25	3	6.0
MMSZ5237B	F2	8.2	7.79	8.61	20	8	500	0.25	3	6.5
MSZ5238B	F3	8.7	8.27	9.14	20	8	600	0.25	3	6.5
MSZ5239B	F4	9.1	8.65	9.56	20	10	600	0.25	3	7.0
MSZ5240B	F5	10	9.50	10.50	20	17	600	0.25	3	8.0
MSZ5241B	H1	11	10.45	11.55	20	22	600	0.25	2.0	8.4
MSZ5242B	H2	12	11.40	12.60	20	30	600	0.25	1.0	9.1
MMSZ5243B	H3	13	12.35	13.65	20	35	600	0.25	0.5	9.8
MMSZ5244B	H4	14	13.30	14.70	20	40	600	0.25	0.1	10.5
MMSZ5245B	H5	15	14.25	15.75	20	45	600	0.25	0.1	11.2
MMSZ5246B	J1	16	15.20	16.80	20	50	600	0.25	0.1	11.9
MMSZ5247B	J2	17	16.15	17.85	20	55	600	0.25	0.1	12.6
MMSZ5248B	J3	18	17.10	18.90	20	60	600	0.25	0.1	13.3
MMSZ5250B	J5	20	19.05	21.05	20	62	600	0.25	0.1	14.0
MMSZ5251B	K1	22	20.90	22.90	20	65	600	0.25	0.1	14.7
MMSZ5252B	K2	24	22.80	25.20	20	68	600	0.25	0.1	15.4
MMSZ5253B	K3	25	23.75	26.25	20	70	600	0.25	0.1	16.1
MMSZ5254B	K4	27	25.65	28.35	20	75	600	0.25	0.1	16.8
MMSZ5255B	K5	28	26.60	29.40	20	80	600	0.25	0.1	17.5
MMSZ5256B	M1	30	28.50	31.50	20	85	600	0.25	0.1	18.2
MMSZ5257B	M2	33	31.35	34.65	20	90	600	0.25	0.1	18.9
MMSZ5258B	M3	36	34.20	37.80	20	95	600	0.25	0.1	19.6
MMSZ5259B	M4	39	37.05	40.95	20	100	600	0.25	0.1	20.3

*Pulse width = 10 ms

Typical Characteristics



[illegible]