

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
60V	9.5mΩ@10V	75A


Feature

- Trench Technology Power MOSFET
- Low $R_{DS(on)}$
- Low Gate Charge
- Low Gate Resistance
- 100% UIS Tested
- 100% ΔV_{DS} Tested

Application


- Power Switching Application

MARKING:




75N06L = Device Code
 XX = Date Code
 Solid Dot = Green Indicator

TO-252-2L



Schematic diagram



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter		Symbol	Value	Unit
Drain - Source Voltage		V_{DS}	60	V
Gate - Source Voltage		V_{GS}	±20	V
Continuous Drain Current ¹	$T_C = 25^\circ\text{C}$	I_D	75	A
Continuous Drain Current ¹	$T_C = 100^\circ\text{C}$	I_D	50	A
Continuous Drain Current ⁶	$T_A = 25^\circ\text{C}$	I_D	13	A
Pulsed Drain Current ²		I_{DM}	225	A
Single Pulsed Avalanche Current ³		I_{AS}	29	A
Single Pulsed Avalanche Energy ³		E_{AS}	210	mJ
Power Dissipation ⁵	$T_C = 25^\circ\text{C}$	P_D	83	W
Thermal Resistance from Junction to Ambient ⁶		$R_{\theta JA}$	50	$^\circ\text{C/W}$
Thermal Resistance from Junction to Case		$R_{\theta JC}$	1.5	$^\circ\text{C/W}$
Junction Temperature and Storage Temperature		T_J, T_{STG}	-55~ +150	$^\circ\text{C}$







MOSFET ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)




Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Off Characteristics						
Drain - Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250μA	60			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 48V, V _{GS} = 0V			1	μA
Gate - Body Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V			±100	nA
On Characteristics ⁴						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	1	1.6	3	V
Drain-Source On-Resistance	R _{DS(on)}	V _{GS} = 10V, I _D = 20A		9.5	11	mΩ
Forward Transconductance	g _{FS}	V _{DS} = 5V, I _D = 20A	20			S
Dynamic Characteristics						
Input Capacitance	C _{iss}	V _{DS} = 30V, V _{GS} = 0V, f = 1MHz		2682		pF
Output Capacitance	C _{oss}			174		
Reverse Transfer Capacitance	C _{rss}			158		
Gate Resistance	R _g	V _{DS} = 0V, V _{GS} = 0V, f = 1MHz		2		Ω
Switching Characteristics						
Total Gate Charge	Q _g	V _{DS} = 30V, V _{GS} = 10V, I _D = 20A		50		nC
Gate-Source Charge	Q _{gs}			15		
Gate-Drain Charge	Q _{gd}			21		
Turn-On Delay Time	t _{d(on)}	V _{DD} = 30V, V _{GS} = 10V, R _L = 1.5Ω R _G = 3Ω		20		ns
Turn-On Rise Time	t _r			12		
Turn-Off Delay Time	t _{d(off)}			44		
Turn-Off Fall Time	t _f			15		
Source - Drain Diode Characteristics						
Diode Forward Voltage ⁴	V _{SD}	V _{GS} = 0V, I _S = 20A			1.2	V


Notes :

- 1.The maximum current rating is limited by package.And device mounted on a large heatsink
- 2.Pulse Test : Pulse Width ≤ 10μs, duty cycle ≤ 1%.
- 3.EAS condition: V_{DD} = 20V, V_{GS} = 10V, L = 0.5mH, R_G = 25Ω Starting T_J = 25°C.
- 4.Pulse Test : Pulse Width ≤ 300μs, duty cycle ≤ 2%.
- 5.The power dissipation P_D is limited by T_{J(MAX)} = 150°C.And device mounted on a large heatsink
- 6.Device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with T_A = 25°C.

Typical Characteristics





TO-252-2L Package Information


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	6.85	7.45	0.27	0.29
B	5.90	6.35	0.23	0.25
C	5.13	5.53	0.20	0.22
D	6.40	6.80	0.25	0.27
E	2.90	3.30	0.11	0.13
F	2.20	2.40	0.09	0.09
G	0.65	0.95	0.03	0.04
H	2.25	2.45	0.09	0.10
I	0.40	0.60	0.02	0.02
J	0°	8°	0°	8°
K	1.65	2.15	0.06	0.08
L	0.45	0.65	0.02	0.03
M	0.00	0.12	0.00	0.00
N	0.60	1.00	0.02	0.04

Attention:

- GreenPower Electronics reserves the right to improve product design function and reliability without notice.
- Any and all semiconductor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.
- GreenPower Electronics products belong to consumer electronics or other civilian electronic products.