

Product Summary

The GESDBH3V3AE1 is designed to protect voltage sensitive electronic components from ESD and other transients. Excellent clamping capability, low leakage, low capacitance, and fast response time, make these parts ideal for ESD protection on designs where board space is at a premium. Because of its small size, it is suited for use in digital cameras, cellular phones, MP3 players and many other portable applications where board space is at a premium.

Feature

- Low reverse stand-off voltage: 3.3V Max.
- Low reverse clamping voltage
- Low leakage current
- Fast response time
- ESD Rating of Class 3(>16KV) Per Human Body Model
- IEC 61000-4-2 Level 4 ESD protection

Application


- Digital cameras
- Portable applications
- Audio and video equipment
- MP3 players
- Mobile phone

Marking:




Front Side
LA=Device Code

DFN0603-2L



Schematic diagram



Absolute Maximum Ratings (Ta=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
IEC 61000-4-2 ESD Voltage	V _{ESD}	±25	kV
IEC 61000-4-2 ESD Voltage		±25	
ESD Voltage		±16	
ESD Voltage		0.4	
Peak Pulse Power	P _{PP}	54	W
Peak Pulse Current	I _{PP}	6	A
Lead Solder Temperature – Maximum (10 Second Duration)	T _L	260	°C
Junction Temperature	T _j	150	°C
Storage Temperature	T _{stg}	-45~ +150	°C

ESD Standards Compliance


IEC61000-4-2 Standard

Contact Discharge		Air Discharge	
Level	Test Voltage kV	Level	Test Voltage kV
1	2	1	2
2	4	2	4
3	6	3	8
4	8	4	15


JESD22-A114-B Standard

ESD Class	Human Body Discharge V
0	0~249
1A	250~499
1B	500~999
1C	1000~1999
2	2000~3999
3A	4000~7999
3B	8000~15999

Contact discharge current waveform per IEC61000-4-2




8/20µs waveform per IEC61000-4-5



Electrical Parameter

Symbol	Parameter
V _C	Clamping Voltage @ I _{PP}
I _{PP}	Peak Pulse Current
V _{BR}	Breakdown Voltage @ I _{BR}
I _{BR}	Test Current
I _R	Reverse Leakage Current @ V _{RWM}
V _{RWM}	Reverse Standoff Voltage



V-I characteristics for a Bi-directional TVS


Electrical Characteristics (T_a=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse stand-off voltage	V _{RWM}				3.3	V
Reverse leakage current	I _R	V _{RWM} =3.3V			0.1	μA
Breakdown voltage	V _{BR} ¹⁾	I _T =1mA	4.0		6.3	V
Clamping voltage	V _{C1} ²⁾	I _{PP} =1A		6	9	V
	V _{C2} ²⁾	I _{PP} =6A		9	12	V
Peak Pulse Current	I _{PP} ²⁾				6	A
Junction capacitance	C _J	V _R =0V, f=1MHz		9	20	pF


- 1) V_{BR} is measured with a pulse test current I_T at an ambient temperature of 25°C
- 2) Surge current waveform per Figure 2.

Typical Characteristics


V_C vs. I_{PP}




I-V Curve




Peak pulse power vs. Pulse time



Power derating vs. Ambient temperature



DFN0603-2L Package Outline Dimensions



	Dimensions In Millimeters		
	Min.	Typ.	Max.
A	0.25	0.30	0.35
B	0.55	0.60	0.65
C	0.27	0.30	0.34
E	-	0.35	-
F	0.20	0.25	0.35
H	0.045 REF		
L	0.13	0.18	0.23
L1	0.045REF		