

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
30V	34mΩ@10V	4A
	37mΩ@4.5V	
	45mΩ@2.5V	


Feature

- TrenchFET Power MOSFET
- Excellent $R_{DS(on)}$ and Low Gate Charge

Application


- DC/DC Converter
- Load Switch for Portable Devices
- Battery Switch

MARKING:

SOT-23


1. GATE
2. SOURCE
3. DRAIN

Schematic diagram


ABSOLUTE MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	±12	V
Continuous Drain Current	I_D	4	A
Pulsed Drain Current ⁽¹⁾	I_{DM}	15	A
Power Dissipation	P_D	0.35	W
Thermal Resistance from Junction to Ambient ⁽²⁾	$R_{\theta JA}$	357	$^{\circ}\text{C/W}$
Junction Temperature	T_J	150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55~ +150	$^{\circ}\text{C}$







MOSFET ELECTRICAL CHARACTERISTICS($T_a=25^{\circ}\text{C}$ unless otherwise noted)




Parameter	Symbol	Test Condition	Min	Type	Max	Unit
STATIC CHARACTERISTICS						
Drain-source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D =250μA	30			V
Zero gate voltage drain current	I _{DSS}	V _{DS} =30V,V _{GS} = 0V			1	μA
Gate-body leakage current	I _{GSS}	V _{GS} =±12V, V _{DS} = 0V			±100	nA
Gate threshold voltage ⁽³⁾	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA	0.5	0.9	1.5	V
Drain-source on-resistance ⁽³⁾	R _{DS(on)}	V _{GS} =10V, I _D =4A		34	52	mΩ
		V _{GS} =4.5V, I _D =3A		37	65	
		V _{GS} =2.5V, I _D =2A		45	85	
Forward tranconductance ⁽³⁾	g _{FS}	V _{DS} =5V, I _D =3.6A		13		S
DYNAMIC CHARACTERISTICS ⁽⁴⁾						
Input Capacitance	C _{iss}	V _{DS} =15V,V _{GS} =0V,f=1MHz		389		pF
Output Capacitance	C _{oss}			54		
Reverse Transfer Capacitance	C _{rss}			40		
Gate resistance	R _g	V _{DS} =0V,V _{GS} =0V,f =1MHz		3.5		Ω
SWITCHING CHARACTERISTICS ⁽⁴⁾						
Turn-on delay time	t _{d(on)}	V _{GS} =10V,V _{DS} =15V, R _L =3.75Ω,R _{GEN} =6Ω		3.5		ns
Turn-on rise time	t _r			1.2		
Turn-off delay time	t _{d(off)}			22		
Turn-off fall time	t _f			2.2		
Total gate charge	Q _g	V _{DS} =15V,V _{GS} =4.5V,I _D =4A		4.4		nC
Gate-source charge	Q _{gs}			0.7		
Gate-drain charge	Q _{gd}			1.3		
SOURCE-DRAIN DIODE CHARACTERISTICS						
Body Diode Voltage ⁽³⁾	V _{SD}	I _S =1A, V _{GS} = 0V			1	V
Continuous Source-Drain Diode Current	I _S	T _C =25℃			1.5	A
Body diode reverse recovery time	t.	I _F =4A,dI/dt=100A/μs		1.3		ns
Body diode reverse recovery charge	Q _{rr}			6.2		nC

Notes:

1. Repetitive rating : Pulse width limited by junction temperature.
2. Surface mounted on FR4 board , $t_s \leq 10s$.
3. Pulse Test : Pulse Width $\leq 80\mu s$, Duty Cycle $\leq 0.5\%$.
4. Guaranteed by design, not subject to producing.

Typical Electrical and Thermal Characteristics




SOT-23 Package Information


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Tape and Reel


SOT-23 Tape and reel

SOT-23 Embossed Carrier Tape




Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer



SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	30,000 pcs	203×203×195	120,000 pcs	438×438×220	