

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
30V	20mΩ@10V	6.0A
	29mΩ@4.5V	



Feature

- High cell density trench N-ch MOSFETs
- Super low gate charge
- Advanced high cell density Trench technology

Application

- Battery protection applications
- Load switch

MARKING:



ABSOLUTE MAXIMUM RATINGS ($T_C=25^{\circ}C$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ¹	I_D	6.0	A
Pulsed Drain Current	I_{DM}	18	A
Power Dissipation	P_D	1.4	W
Thermal Resistance from Junction to Ambient ²	$R_{\theta JA}$	89	$^{\circ}C/W$
Junction Temperature	T_J	150	$^{\circ}C$
Storage Temperature	T_{STG}	-55~ +150	$^{\circ}C$







MOSFET ELECTRICAL CHARACTERISTICS (T_J=25°C unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Static Characteristics						
Drain-source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = -250μA	30			V
Zero gate voltage drain current	I _{DSS}	V _{DS} = 24V, V _{GS} = 0V			1	μA
Gate-body leakage current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V			±100	nA
Gate threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250μA	1.0	1.4	3.0	V
Drain-source on-resistance ³	R _{DS(on)}	V _{GS} = 10V, I _D = 6.0A		20	30	mΩ
		V _{GS} = 4.5V, I _D = 5.0A		29	42	
Forward transconductance	g _{FS}	V _{DS} = 5V, I _D = 5A	8	12		S
Dynamic characteristics⁴						
Input Capacitance	C _{iss}	V _{DS} = 15V, V _{GS} = 0V, f = 1MHz		633		pF
Output Capacitance	C _{oss}			65		
Reverse Transfer Capacitance	C _{rss}			55		
Total gate charge	Q _g	V _{DS} = 15V, I _D = 5.8A, V _{GS} = 4.5V		9.5		nC
Gate-source charge	Q _{gs}			1.5		
Gate-drain charge	Q _{gd}			3		
Gate resistance	R _g	V _{DS} = 0V, V _{GS} = 0V, f = 1MHz		4		Ω
Switching Characteristics⁴						
Turn-on delay time	t _{d(on)}	V _{DD} = 15V, R _L = 2.7Ω V _{GS} = 10V, R _{GEN} = 3Ω		3.3		ns
Turn-on rise time	t _r			4.8		
Turn-off delay time	t _{d(off)}			26		
Turn-off fall time	t _f			4		
Source-Drain Diode characteristics						
Diode Forward voltage ³	V _{SD}	V _{GS} = 0V, I _S = 1A		0.76	1	V




Notes:

1. Repetitive Rating : Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t < 5 sec.
3. Pulse Test : Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
4. Guaranteed by design, not subject to production testing.

Typical Electrical and Thermal Characteristics




SOP8 Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.007	0.010
D	4.800	5.000	0.189	0.197
e	1.270 (BSC)		0.050 (BSC)	
E	5.800	6.200	0.228	0.244
E1	3.800	4.000	0.150	0.157
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°


SOP8 Tape and Reel

SOP8 Embossed Carrier Tape




Dimensions are in millimeter										
Pkg type	a	B	C	d	E	F	P0	P	P1	W
SOP8	6.40	5.40	2.10	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

SOP8 Tape Leader and Trailer



SOP8 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
13" Dia	Ø330.00	100.00	13.00	R151.00	R56.00	R6.50	12.40	17.60

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
4,000 pcs	13 inch	8,000 pcs	360×360×65	64,000 pcs	565×380×390	