

Introduction

The GPL6331A series are a group of positive voltage regulators manufactured by CMOS technologies with low power consumption and low dropout voltage, which provide large output currents even when the difference of the input-output voltage is small. The GPL6331A series can deliver 300mA output current and allow an input voltage as high as 18V. The series are very suitable for the battery-powered equipment, such as RF applications and other systems requiring a quiet voltage source.


Features

- Low Quiescent Current: 2 μ A
- Operating Voltage Range: 2.5V~18V
- Output Current: 300mA
- Low Dropout Voltage: 160mV@100mA (V_{OUT}=5V)
- Output Voltage: 1.2~5.0V
- High Accuracy: $\pm 2\%/\pm 1\%$ (Typ.)
- High Power Supply Rejection Ratio: 65dB@1kHz
- Low Output Noise: $27 \times V_{OUT} \mu V_{RMS}$ (10Hz~100kHz)
- Excellent Line and Load Transient Response
- Built-in Current Limiter, Short-Circuit Protection
- Over-Temperature Protection

Applications

- Cordless Phones
- Radio control systems
- Laptop, Palmtops and PDAs
- Single-lens reflex DSC
- PC peripherals with memory
- Wireless Communication Equipment
- Portable Audio Video Equipment
- Car Navigation Systems
- LAN Cards
- Ultra-Low Power Microcontrollers






Block Diagram



Order Information

GPL6331①②③A④

Designator	Symbol	Description
①②③	Integer	Output Voltage e.g. 1.8V=①:V, ②:1, ③:8
④	K3	Package:SOT-23-3L
	K5	Package:SOT-23-5L
	KE	Package:SOT-89-3L
	KT	Package:SOT-89-5L
	H1	Package:DFN1*1-4L

Pin Configuration
SOT-23-3L

SOT-23-5L

DFN1*1-4

SOT-89-3L

SOT-89-5

SOT-23-3L & SOT-89-3L

Pin Number		Pin Name	Function
SOT-23-3L	SOT-89-3L		
1	1	V _{SS}	Ground
2	3	V _{OUT}	Output
3	2	V _{IN}	Power input

SOT-23-5L & SOT-89-5L

Pin Number		Pin Name	Function
SOT-23-5L	SOT-89-5L		
1	5	V _{IN}	Power Input Pin
2	2	V _{SS}	Ground
3	4	CE	Chip Enable Pin
4	3	NC	No Connection
5	1	V _{OUT}	Output Pin

WBFBP-04C(DFN1*1-4)

Pin Number	Pin Name	Function
1	V _{IN}	Power Input Pin
2	V _{SS}	Ground
3	CE	Chip Enable Pin
4	V _{OUT}	Output Pin

Absolute Maximum Ratings¹⁾ ($T_a=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Ratings	Units
Input Voltage ²⁾	V_{IN}	-0.3~24	V
Output Voltage ²⁾	V_{OUT}	-0.3~10	V
CE Pin Voltage	V_{CE}	-0.3~24	V
Output Current	I_{OUT}	300	mA
Power Dissipation	P_D	0.4	W
Operating Junction Temperature Range ³⁾	T_J	-40~125	$^\circ\text{C}$
Storage Temperature	T_{stg}	-40~125	$^\circ\text{C}$
Lead Temperature(Soldering, 10 sec)	T_{solder}	260	$^\circ\text{C}$
ESD rating ⁴⁾	Human Body Model -(HBM)	2	kV
	Machine Model- (MM)	200	V

- 1) Stresses beyond those listed under *absolute maximum ratings* may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *recommended operating conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- 2) All voltages are with respect to network ground terminal.
- 3) This GPL6331A includes over temperature protection that is intended to protect the device during momentary overload. Junction temperature will exceed 125°C when over temperature protection is active. Continuous operation above the specified maximum operating junction temperature may impair device reliability.
- 4) ESD testing is performed according to the respective JESD22 JEDEC standard. The human body model is a 100 pF capacitor discharged through a 1.5kΩ resistor into each pin. The machine model is a 200pF capacitor discharged directly into each pin.


Electrical Characteristics
GPL6331A Series ($V_{IN}=V_{OUT}+1V$, $C_{IN}=C_{OUT}=1\mu F$, $T_A=25^\circ C$, unless otherwise specified)







Parameter	Symbol	Conditions	Min.	Typ. ⁵⁾	Max.	Units
Input Voltage	V_{IN}		2.5		18	V
Output Voltage Range	V_{OUT}		1.2		5	V
DC Output Accuracy		$I_{OUT}=1mA$	-2		2	%
			-1		1	%
Dropout Voltage	V_{dif} ⁶⁾	$I_{OUT}=100mA, V_{OUT}=5V$		160		mV
Supply Current	I_{SS}	$I_{OUT}=0A$		2	5	μA
Line Regulation	$\frac{\Delta V_{OUT}}{V_{OUT} \times \Delta V_{IN}}$	$I_{OUT}=10mA$ $V_{OUT}+1V \leq V_{IN} \leq 18V$		0.01	0.3	%/V
Load Regulation	$\frac{\Delta V_{OUT}}{V_{IN}}$	$V_{IN}=V_{OUT}+1V$, $1mA \leq I_{OUT} \leq 100mA$		10		mV
Temperature Coefficient	$\frac{\Delta V_{OUT}}{V_{OUT} \times \Delta T_A}$	$I_{OUT}=10mA$, $-40^\circ C < T_A < 125^\circ C$		50		ppm
Output Current Limit	I_{LIM}	$V_{OUT}=0.5 \times V_{OUT(\text{Normal})}$, $V_{IN}=7V$	350	500		mA
Short Current	I_{SHORT}	$V_{OUT}=V_{SS}$		25		mA
Power Supply Rejection Ratio	PSRR	$I_{OUT}=50mA$	100Hz	80		dB
			1kHz	65		
			10kHz	50		
			100kHz	45		
Output Noise Voltage	V_{ON}	BW=10Hz to 100kHz		$27 \times V_{OUT}$		μV_{RMS}
Thermal Shutdown Temperature	T_{SD}			150		$^\circ C$
Thermal Shutdown Hysteresis	ΔT_{SD}			20		$^\circ C$
Standby Current	I_{STBY}	$CE=V_{SS}$			0.2	μA
CE "High" Voltage	$V_{CE(H)}$		1.5		V_{IN}	V
CE "Low" Voltage	$V_{CE(L)}$				0.3	V
CE "High" Current	$I_{CE(H)}$	$V_{CE}=\text{High}$			0.2	μA


5) Typical numbers are at $25^\circ C$ and represent the most likely norm.

6) V_{dif} : The Difference Of Output Voltage And Input Voltage When Input Voltage Is Decreased Gradually Till Output Voltage Equals To 98% Of V_{OUT} (E).


7)

Typical Application Circuit



Typical Performance Characteristics
Output Voltage vs. Temperature

Output Voltage vs. Output Current

Output Voltage vs. Input Voltage

Ground Current VS. Load Current

Dropout Voltage vs. Load Current

PSRR vs. Frequency($V_{in}=6V+aV_{P-P}AC$)


SOT-23-3L Package Outline Dimensions



Symbol	Dimensions in millimeters		
	Min.	Typ.	Max.
A	1.050	-	1.250
A1	0.000	-	0.100
A2	1.050	-	1.150
b	0.300	-	0.500
c	0.100	-	0.200
D	2.820	-	3.020
E	1.500	-	1.700
E1	2.650	-	2.950
e	0.950TYP		
e1	1.800	-	2.000
L	0.300	-	0.600
θ	0°	-	8°

SOT-23-3L Suggested Pad Layout (Unit: mm)

Notes:


1. General tolerance: $\pm 0.05\text{mm}$.
2. The pad layout is for reference purposes only.

SOT-23-5L Package Outline Dimensions



Symbol	Dimensions In Millimeters	
	Min.	Max.
A	1.050	1.250
A1	0.000	0.100
A2	1.050	1.150
b	0.300	0.500
c	0.100	0.200
D	2.820	3.020
E	1.500	1.700
E1	2.650	2.950
e	0.950(BSC)	
e1	1.800	2.000
L	0.300	0.600
θ	0°	8°

SOT-23-5L Suggested Pad Layout (Unit: mm)

Notes:


1. General tolerance: $\pm 0.05\text{mm}$.
2. The pad layout is for reference purposes only.

SOT-89-3L Package Outline Dimensions


Symbol	Dimensions in millimeters		Dimensions in inches	
	Min.	Max.	Min.	Max.
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.197
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550REF		0.061REF	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500TYP		0.060TYP	
e1	3.000TYP		0.118TYP	
L	0.900	1.200	0.035	0.047

SOT-89-5L Package Outline Dimensions


Symbol	Dimensions in millimeters		Dimensions in inches	
	Min.	Max.	Min.	Max.
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.197
b1	0.360	0.560	0.014	0.022
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.400	1.800	0.055	0.071
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500TYP		0.060TYP	
e1	2.900	3.100	0.114	0.122
L	0.900	1.100	0.035	0.043

DFN1*1-4L Package Outline Dimensions


Symbol	Dimensions in millimeters	
	Min.	Max.
A	0.950	1.050
B	0.320	0.420
C	0.950	1.050
D	0.600	0.700
E	0.175	0.275
F	0.170	0.270
G	0.440	0.540
H	0.440	0.540
I	0.140	0.240