

Product Summary


$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
15V	8.5mΩ@4.5V	8A
	11.0mΩ@2.5V	

Feature

- Trench Technology Power MOSFET
- Low $R_{DS(ON)}$
- Low Gate Charge



Application

- Battery Protection
- Load Switch
- Power Management

MARKING:


L1508 = Device Code

XX = Date Code

SOT-23-6L

Schematic diagram

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)







Parameter		Symbol	Value	Unit
Drain - Source Voltage		V_{DS}	15	V
Gate - Source Voltage		V_{GS}	± 10	V
Continuous Drain Current	$T_A = 25^\circ\text{C}$	I_D	8	A
Pulsed Drain Current ¹		I_{DM}	32	A
Power Dissipation ³	$T_A = 25^\circ\text{C}$	P_D	1.5	W
Thermal Resistance from Junction to Ambient ⁴		$R_{\theta JA}$	83.3	$^\circ\text{C/W}$
Junction Temperature		T_J	150	$^\circ\text{C}$
Storage Temperature		T_{STG}	-55~ +150	$^\circ\text{C}$


MOSFET ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Off Characteristics						
Drain - source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250μA	15			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 12V, V _{GS} = 0V			1	μA
Gate - body Leakage Current	I _{GSS}	V _{GS} = ±10V, V _{DS} = 0V			±5	μA
On Characteristics ²						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	0.4	0.7	1.0	V
Drain - source On-resistance	R _{DS(on)}	V _{GS} = 4.5V, I _D = 3A	7.0	8.5	11.0	mΩ
		V _{GS} = 2.5V, I _D = 3A	8.0	11.0	16.0	
Forward Transconductance	g _{FS}	V _{DS} = 5V, I _D = 8A		18		S
Dynamic Characteristics						
Input Capacitance	C _{iSS}	V _{DS} = 7.5V, V _{GS} = 0V, f = 500KHz		1000		pF
Output Capacitance	C _{oSS}			110		
Reverse Transfer Capacitance	C _{rSS}			30		
Switching Characteristics						
Total Gate Charge	Q _g	V _{DS} = 7.5V, V _{GS} = 4.5V, I _D = 3A		20		nC
Gate-source Charge	Q _{gs}			3		
Gate-drain Charge	Q _{gd}			7		
Turn-on Delay Time	t _{d(on)}	V _{DD} = 7.5V, V _{GS} = 4.5V, R _L = 2.5Ω, R _G = 2Ω		3		ns
Turn-on Rise Time	t _r			9		
Turn-off Delay Time	t _{d(off)}			62		
Turn-off Fall Time	t _f			120		
Source - Drain Diode Characteristics						
Diode Forward Voltage ²	V _{SD}	V _{GS} = 0V, I _S = 1.0A			1.2	V

Notes :

- 1.Pulse Test : Pulse Width ≤ 10μs, duty cycle ≤ 1%.
- 2.Pulse Test : Pulse Width ≤ 300μs, duty cycle ≤ 2%.
- 3.The power dissipation P_D is limited by T_{J(MAX)} = 150°C.
- 4.Device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with T_A = 25°C.

Typical Characteristics


SOT-23-6L Package Information


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.050	1.250	0.041	0.049
A1	0	0.150	0.000	0.006
A2	1.050	1.250	0.041	0.049
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	2.650	2.950	0.104	0.116
E1	1.500	1.700	0.059	0.067
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
L1	0.600REF		0.024REF	
θ	0°	8°	0°	8°