

Product Summary

The GESDBL3V3Y1 is designed to protect voltage sensitive electronic components from ESD and other transients. Excellent clamping capability, low leakage, low capacitance, and fast response time, make these parts ideal for ESD protection on designs where board space is at a premium. Because of its small size, it is suited for use in digital cameras, cellular phones, MP3 players and many other portable applications where board space is at a premium.

Feature

- Low Reverse Stand-Off Voltage: 3.3V Max.
- Low Reverse Clamping Voltage
- Ultra-Low Leakage Current
- Fast Response Time
- IEC 61000-4-2 Level 4 ESD Protection

Application


- Digital Cameras
- Portable Applications
- Audio And Video Equipment
- Mobile Phone

Marking:




Front Side
X1=Device Code

DFN1006-2L



Schematic diagram



Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
IEC 61000-4-2 ESD Voltage Air Model	V_{ESD}	± 30	kV
IEC 61000-4-2 ESD Voltage Contact Model		± 30	
JESD22-A114-B ESD Voltage Per Human Body Model		± 16	
ESD Voltage Machine Model		± 0.4	
Peak Pulse Power (8/20 μs)	P_{pk}	70	W
Peak Pulse Current (8/20 μs)	I_{PP}	5	A
Junction Temperature	T_J	$-55 \sim +125$	$^{\circ}\text{C}$
Storage Temperature	T_{stg}	$-55 \sim +150$	$^{\circ}\text{C}$

ESD standards compliance


IEC61000-4-2 Standard

Contact Discharge		Air Discharge	
Level	Test Voltage kV	Level	Test Voltage kV
1	2	1	2
2	4	2	4
3	6	3	8
4	8	4	15


JESD22-A114-B Standard

ESD Class	Human Body Discharge V
0	0~249
1A	250~499
1B	500~999
1C	1000~1999
2	2000~3999
3A	4000~7999
3B	8000~15999

Contact discharge current waveform per IEC61000-4-2




8/20 μs waveform per IEC61000-4-5



Electrical Parameter

Symbol	Parameter
V _C	Clamping Voltage @ I _{PP}
I _{PP}	Peak Pulse Current
V _{BR}	Breakdown Voltage @ I _{BR}
I _{BR}	Test Current
I _R	Reverse Leakage Current @ V _{RWM}
V _{RWM}	Reverse Standoff Voltage



V-I characteristics for a Bi-directional TVS





Electrical Characteristics (T_A=25°C unless otherwise specified)


Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse Stand-Off Voltage	V _{RWM} ¹⁾				3.3	V
Reverse Leakage Current	I _R	V _{RWM} = 3.3V			1	μA
Breakdown Voltage	V _{BR}	I _T = 1mA	4.0		6.8	V
Clamping Voltage	V _C ²⁾	I _{PP} = 5A			14	V
Junction Capacitance	C _J	V _R = 0V, f = 1MHz			20	pF

Notes:


- 1) Other voltages available upon request.
- 2) Non-repetitive current pulse 8/20μs exponential decay waveform according to IEC61000-4-5

Typical Characteristics




DFN1006-2L Package Outline Dimensions


TOP VIEW
[顶视图]



BOTTOM VIEW
[底视图]



SIDE VIEW
[侧视图]

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.400	0.550	0.016	0.022
A1	0.000	0.050	0.000	0.002
D	0.950	1.050	0.037	0.041
E	0.550	0.650	0.022	0.026
b	0.400	0.600	0.016	0.024
e	0.65 TYP		0.026 TYP	
L1	0.05 REF		0.002 REF	
L	0.200	0.300	0.008	0.012

Attention:

- GreenPower Electronics reserves the right to improve product design function and reliability without notice.
- Any and all semiconductor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.
- GreenPower Electronics products belong to consumer electronics or other civilian electronic products.