

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
80V	3.8mΩ@10V	115A


Feature

- Split Gate Trench Technology
- Low $R_{DS(on)}$
- Low Gate Charge
- Low Gate Resistance
- 100% UIS Tested


Application

- Power Switching Application
- Motor Driving
- Power Management

PDFN5X6-8L



Schematic diagram



Package Marking and Ordering Information

Part Number	Package	Marking	Packing	Reel Size	Tape Width	Qty
GPT038N08NNC	PDFN5X6-8L	T038N08N	Reel & Tape	330mm	12mm	5000pcs

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter		Symbol	Value	Unit
Drain-Source Voltage		V_{DS}	80	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current ¹	$T_C = 25^\circ\text{C}$	I_D	115	A
	$T_C = 100^\circ\text{C}$		73	
Pulsed Drain Current ²		I_{DM}	460	A
Single Pulsed Avalanche Current ³		I_{AS}	36	A
Single Pulsed Avalanche Energy ³		E_{AS}	324	mJ
Power Dissipation ⁵		P_D	125	W
		$T_C = 25^\circ\text{C}$		
Thermal Resistance from Junction to Ambient ⁶		$R_{\theta JA}$	52	°C/W
Thermal Resistance from Junction to Case		$R_{\theta JC}$	1.0	°C/W
Junction Temperature		T_J	150	°C
Storage Temperature		T_{STG}	-55~ +150	°C







MOSFET ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)




Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	80			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 80V, V_{GS} = 0V$			1	μA
Gate-Body Leakage Current	I_{GSS}	$V_{GS} = \pm 20V, V_{DS} = 0V$			± 100	nA
On Characteristics ⁴						
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	2	2.8	4	V
Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 20A$		3.8	5.0	m Ω
Dynamic Characteristics						
Input Capacitance	C_{iss}	$V_{DS} = 40V, V_{GS} = 0V, f = 1MHz$		3155		pF
Output Capacitance	C_{oss}			616		
Reverse Transfer Capacitance	C_{rss}			24		
Gate Resistance	R_g	$V_{DS} = 0V, V_{GS} = 0V, f = 1MHz$		2.5		Ω
Switching Characteristics						
Total Gate Charge	Q_g	$V_{DS} = 40V, V_{GS} = 10V, I_D = 20A$		47		nC
Gate-Source Charge	Q_{gs}			13		
Gate-Drain Charge	Q_{gd}			12		
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = 40V, V_{GS} = 10V, R_G = 3\Omega, R_L = 2\Omega$		16		ns
Turn-On Rise Time	t_r			23		
Turn-Off Delay Time	$t_{d(off)}$			32		
Turn-Off Fall Time	t_f			11		
Source-Drain Diode Characteristics						
Diode Forward Voltage ⁴	V_{SD}	$V_{GS} = 0V, I_S = 20A$			1.2	V







Notes:


- 1.The maximum current rating is limited by package. And device mounted on a large heatsink.
- 2.Pulse Test: Pulse Width $\leq 10\mu s$, duty cycle $\leq 1\%$.
- 3.EAS condition: $V_{DD} = 80V, V_{GS} = 10V, L = 0.5mH, R_G = 25\Omega$ Starting $T_J = 25^\circ\text{C}$.
- 4.Pulse Test: Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.
- 5.The power dissipation P_D is limited by $T_{J(MAX)} = 150^\circ\text{C}$. And device mounted on a large heatsink.
- 6.Device mounted on $1in^2$ FR-4 board with 2oz. Copper, in a still air environment with $T_A = 25^\circ\text{C}$.

Typical Characteristics





Gate Charge Test Circuit & Waveform

Resistive Switching Test Circuit & Waveform

Unclamped Inductive Switching (UIS) Test Circuit & Waveforms


PDFN5X6-8L Package Information


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.100	0.035	0.043
b	0.330	0.510	0.013	0.020
c	0.200	0.300	0.008	0.012
D	4.820	5.220	0.190	0.206
D2	3.910	4.110	0.154	0.162
E	5.900	6.100	0.232	0.240
E1	5.700	5.800	0.224	0.228
E2	3.370	3.570	0.133	0.141
e	1.270REF		0.050REF	
H	0.520	0.720	0.020	0.028
D1	4.800	5.000	0.189	0.197
L	0.510	0.710	0.020	0.028
a	0°	10°	0°	10°

Attention:

- GreenPower Electronics reserves the right to improve product design function and reliability without notice.
- Any and all semiconductor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.
- GreenPower Electronics products belong to consumer electronics or other civilian electronic products.