

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
68V	6.2mΩ@10V	90A


Feature

- Split Gate Trench Technology
- Low $R_{DS(on)}$
- Low Gate Charge
- Low Gate Resistance
- 100% UIS Tested


Application

- Load Switch
- PWM Application
- Power Management

TO-252-2L



Schematic diagram



Package Marking and Ordering Information

Part Number	Package	Marking	Packing	Reel Size	Tape Width	Qty
GPM062NE6NTF	TO-252-2L	M062NE6N	Reel & Tape	330mm	16mm	2500pcs

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter		Symbol	Value	Unit
Drain - Source Voltage		V_{DS}	68	V
Gate - Source Voltage		V_{GS}	±20	V
Continuous Drain Current ¹	$T_C = 25^\circ\text{C}$	I_D	90	A
	$T_C = 100^\circ\text{C}$	I_D	56	A
Pulsed Drain Current ²		I_{DM}	360	A
Single Pulsed Avalanche Current ³		I_{AS}	37	A
Single Pulsed Avalanche Energy ³		E_{AS}	342	mJ
Power Dissipation ⁵		P_D	109	W
		$T_C = 25^\circ\text{C}$		
Thermal Resistance from Junction to Ambient ⁶		$R_{\theta JA}$	40	$^\circ\text{C/W}$
Thermal Resistance from Junction to Case		$R_{\theta JC}$	1.15	$^\circ\text{C/W}$
Junction Temperature		T_J	150	$^\circ\text{C}$
Storage Temperature		T_{STG}	-55~ +150	$^\circ\text{C}$







MOSFET ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)




Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Off Characteristics						
Drain - Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250μA	68			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 68V, V _{GS} = 0V			1	μA
Gate - Body Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V			±100	nA
On Characteristics ⁴						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	2	3	4	V
Drain-source On-resistance	R _{DS(on)}	V _{GS} = 10V, I _D = 30A		6.2	7.5	mΩ
Dynamic Characteristics						
Input Capacitance	C _{iss}	V _{DS} = 35V, V _{GS} = 0V, f = 1MHz		5070		pF
Output Capacitance	C _{oss}			241		
Reverse Transfer Capacitance	C _{rss}			200		
Gate Resistance	R _g	V _{DS} = 0V, V _{GS} = 0V, f = 1MHz		1		Ω
Switching Characteristics						
Total Gate Charge	Q _g	V _{DS} = 35V, V _{GS} = 10V, I _D = 30A		92		nC
Gate-source Charge	Q _{gs}			24		
Gate-drain Charge	Q _{gd}			25		
Turn-on Delay Time	t _{d(on)}	V _{DD} = 35V, V _{GS} = 10V, I _D = 30A, R _G = 3Ω		21		ns
Turn-on Rise Time	t _r			30		
Turn-off Delay Time	t _{d(off)}			42		
Turn-off Fall Time	t _f			15		
Source - Drain Diode Characteristics						
Diode Forward Voltage ⁴	V _{SD}	V _{GS} = 0V, I _S = 30A			1.2	V


Notes :

- 1.The maximum current rating is limited by package.And device mounted on a large heatsink
- 2.Pulse Test : Pulse Width $\leq 10\mu s$, duty cycle $\leq 1\%$.
- 3.EAS condition: $V_{DD} = 34V, V_{GS} = 10V, L = 0.5mH, R_G = 25\Omega$ Starting $T_J = 25^\circ\text{C}$.
- 4.Pulse Test : Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.
- 5.The power dissipation P_D is limited by $T_{J(MAX)} = 150^\circ\text{C}$.And device mounted on a large heatsink
- 6.Device mounted on $1in^2$ FR-4 board with 2oz. Copper, in a still air environment with $T_A = 25^\circ\text{C}$.

Typical Characteristics





TO-252-2L Package Information


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
b	0.635	0.860	0.025	0.034
c	0.460	0.580	0.018	0.023
D	6.500	6.700	0.256	0.264
D1	5.100	5.460	0.201	0.215
D2	4.830REF		0.190REF	
E	6.000	6.300	0.236	0.248
e	2.186	2.386	0.086	0.094
L	9.712	10.312	0.382	0.406
L1	2.900REF		0.114REF	
L2	1.400	1.700	0.055	0.067
L3	1.600REF		0.063REF	
L4	0.600	1.000	0.024	0.039
Φ	1.100	1.300	0.043	0.051
θ	0°	8°	0°	8°
h	0.000	0.300	0.000	0.012
V	5.250REF		0.207REF	

Attention:

- GreenPower Electronics reserves the right to improve product design function and reliability without notice.
- Any and all semiconductor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.
- GreenPower Electronics products belong to consumer electronics or other civilian electronic products.