

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
-40V	10mΩ@-10V	-50A
	14mΩ@-4.5V	


Feature

- Trench Technology Power MOSFET
- Low $R_{DS(ON)}$
- Low Gate Charge
- Low Gate Resistance
- 100% UIS Tested
- 100% ΔV_{DS} Tested


Application

- Power Switching Application

PDFN5X6-8L



Schematic diagram



MARKING:



M100P04L = Device Code
XX = Date Code
Solid Dot = Green Indicator

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter		Symbol	Value	Unit
Drain-Source Voltage		V_{DS}	-40	V
Gate-Source Voltage		V_{GS}	± 28	V
Continuous Drain Current ¹	$T_C = 25^\circ\text{C}$	I_D	-50	A
	$T_C = 100^\circ\text{C}$	I_D	-32	A
Pulsed Drain Current ²		I_{DM}	-200	A
Single Pulsed Avalanche Current ³		I_{AS}	-23	A
Single Pulsed Avalanche Energy ³		E_{AS}	132	mJ
Power Dissipation ⁵	$T_C = 25^\circ\text{C}$	P_D	42	W
Thermal Resistance from Junction to Ambient ⁶		$R_{\theta JA}$	65	$^\circ\text{C/W}$
Thermal Resistance from Junction to Case		$R_{\theta JC}$	3	$^\circ\text{C/W}$
Junction Temperature		T_J	150	$^\circ\text{C}$
Storage Temperature		T_{STG}	-55~ +150	$^\circ\text{C}$







MOSFET ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)




Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = -250\mu A$	-40			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = -40V, V_{GS} = 0V$			-1	μA
Gate-Body Leakage Current	I_{GSS}	$V_{GS} = \pm 20V, V_{DS} = 0V$			± 100	nA
On Characteristics ⁴						
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = -250\mu A$	-1	-1.6	-3	V
Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS} = -10V, I_D = -18A$		10	14	m Ω
		$V_{GS} = -4.5V, I_D = -12A$		14	19	
Dynamic Characteristics						
Input Capacitance	C_{iss}	$V_{DS} = -20V, V_{GS} = 0V, f = 1MHz$		2603		pF
Output Capacitance	C_{oss}			254		
Reverse Transfer Capacitance	C_{rss}			220		
Gate Resistance	R_g	$V_{DS} = 0V, V_{GS} = 0V, f = 1MHz$		9.8		Ω
Switching Characteristics						
Total Gate Charge	Q_g	$V_{DS} = -20V, V_{GS} = -10V, I_D = -20A$		51		nC
Gate-Source Charge	Q_{gs}			7.2		
Gate-Drain Charge	Q_{gd}			11		
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = -20V, V_{GS} = -10V, I_D = -20A, R_G = 3\Omega$		15		ns
Turn-On Rise Time	t_r			21		
Turn-Off Delay Time	$t_{d(off)}$			33		
Turn-Off Fall Time	t_f			11		
Source-Drain Diode Characteristics						
Diode Forward Voltage ⁴	V_{SD}	$V_{GS} = 0V, I_S = -10A$			-1.2	V


Notes:

1. The maximum current rating is limited by package. And device mounted on a large heatsink.
2. Pulse Test: Pulse Width $\leq 10\mu s$, duty cycle $\leq 1\%$.
3. E_{AS} condition: $V_{DD} = -20V, V_{GS} = -10V, L = 0.5mH, R_G = 25\Omega$ Starting $T_J = 25^\circ\text{C}$.
4. Pulse Test: Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.
5. The power dissipation P_D is limited by $T_{J(MAX)} = 150^\circ\text{C}$. And device mounted on a large heatsink.
6. Device mounted on $1in^2$ FR-4 board with 2oz. Copper, in a still air environment with $T_A = 25^\circ\text{C}$.

Typical Characteristics





PDFN5X6-8L Package Information


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	5.900	6.100	0.232	0.240
a	3.910	4.110	0.154	0.162
A2	5.700	5.800	0.224	0.228
B	4.900	5.100	0.193	0.201
b	3.375	3.575	0.133	0.141
B1	4.800	5.000	0.189	0.197
C	0.900	1.000	0.035	0.039
L	0.300	0.500	0.014	0.018
l	0.060	0.200	0.002	0.008
L1	1.100	-	0.043	-
l1	-	0.100	-	0.004
L2	1.170	1.370	0.046	0.054
L4	0.210	0.340	0.008	0.013
L6	0.510	0.710	0.020	0.028
L7	0.510	0.710	0.020	0.028
P	1.150	1.450	0.045	0.057
Φ	1.100	1.300	0.043	0.051
θ	8°	12°	8°	12°

Attention:

- GreenPower Electronics reserves the right to improve product design function and reliability without notice.
- Any and all semiconductor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.
- GreenPower Electronics products belong to consumer electronics or other civilian electronic products.